

Specification					
080A15	En 32B	●	●	●	
070M20	En 3	●	●	●	
080M30	En 5	●			
080M40	En 8	●			
080A42	En 8D	●			
070M55	En9	●			
150M19	En14	●			
230M07	En 1A	●		●	●
230M07Pb	En 1APb	●	●		●
212A42	En 8DM	●			●
214M15	En 202	●			
605M36	En 16	●			
708M40	En 19	●			
709M40	En 19	●			
817M40	En 24	●			
606M36	En 16M	●			●
655M13	En 36 A	●			
832M13	En 36 C	●			
SAE 4140		●			
SAE 8620		●			
BS 4360.55C		●			
BSEN 10025 Grade	S235	●	●	●	
	S275	●	●	●	
	S355	●			
BSEN 10083 Grade	C35	●			
	C40	●			
	C45	●			
	C55	●			
	42CrMo4	●			
BSEN 10084 Grade	16MnCr5	●			
BSEN 10277-3 Grade	11SMn30	●			●
	11SMn30 Pb	●			●

Round Bar is available as Bright Drawn Bar and also Turned Bar.

Material can be supplied in one of the following conditions:

- Bright Drawn or Turned
- Hardened and tempered to your requirements.
- Bright Annealed
- Bright Normalised
- Bright Stress Relieved

Specification					
080A15	En 32B	●	●	●	
070M20	En 3	●	●	●	
080M30	En 5	●	●		
080M40	En 8	●	●		
080A42	En 8D	●	●		
070M55	En9	●			
150M19	En14	●	●		
230M07	En 1A	●			●
230M07Pb	En 1APb	●			●
212A42	En 8DM	●			●
214M15	En 202	●			
605M36	En 16	●	●		
708M40	En 19	●	●		
709M40	En 19	●	●		
817M40	En 24	●	●		
826M40	En 26	●	●		
606M36	En 16M	●			
655M13	En36 A	●			
832M13	En 36 C	●			
SAE 4140		●	●		
SAE 8620		●	●		
BS 4360.55C		●	●		
BSEN 10025 Grade	S235	●	●	●	
	S275	●	●	●	
	S355	●	●	●	
BSEN 10083 Grade	C35	●			
	C40	●	●		
	C45	●	●		
	C55	●	●		
	42CrMo4	●	●		
BSEN 10084	16MnCr5	●			
BSEN 10087 Grade	11SMn30	●			●
	11SMn30Pb	●			●

Material can be supplied in the following conditions:

- As-Rolled
- Hardened and Tempered to customer requirement.
- Annealed
- Normalised
- Stress Relieved

Stock is normally held in one of the following conditions:

- As-Rolled
- Hardened and Tempered to all standard conditions.